



R&R industry quality keyboard IKMF2SV5-1HE
– for harsh environment -

housing 19" drawer keyboard
approx. 11° tiltable
aluminium colourless anodized

dimension (W x H x D) approx. 483 x 44 x 310 mm



interface USB, PS/2
layout WIN95

IKMF2SV5-1HE

Ob der Eck 4 · D-78148 Gütenbach · Telefon (07723) 9186-0 · Telefax (07723)9186-30

[DNR12580_EN.DOC REV.02 - 03.05.2014](#)
WWW.RURGMBH.DE INFO@RURGMBH.DE

Push button R&R push button V5, dustproof, waterproof sealed contact and guiding
longlife silicon rubber switches with clear actuation point.
DNR 4715 1.5N, 1.2mm, 2 Million strokes
DNR 3374 1N, 3mm, 3 Million strokes
DNR 4045 3N, 3mm, 2 Million strokes

Keycap Type V5, die-cast zinc, nickel plated
Protection class **All around I P 65**, dustproof, waterproof



Working temperature -30°C up to +70°C
Warning Use gloves for the extended temperature range
Weight Approx. 6 kg
connector Mini-DIN 06 (PS2) or USB-A 3 m Kabel
Cable length 3m
layout german, US, french

IKMF2SV5-1HE

Ob der Eck 4· D-78148 Gütenbach · Telefon (07723) 9186-0 · Telefax (07723)9186-30

[DNR12580_EN.DOC REV.02 - 03.05.2014](#)

WWW.RURGBMH.DE INFO@RURGBMH.DE